

# HAVA Wall-Mounted Indoor Unit

## HHXI Series



### **One indoor unit, multiple configurations**

The HHXI indoor unit is compatible with both 1-to-1 systems and multi-system (Free-Match) configurations, offering greater flexibility and significantly improving inventory management for suppliers.





## Low noise

Optimized airflow paths and an enhanced internal duct design allow the indoor unit to operate with exceptionally low noise levels, reaching as little as 19 dB(A).



## **Energy efficiency in operation and standby**

The HHXI indoor unit features an on-demand energy-saving operating profile and an ultra-low 1-watt standby power draw, both contributing to reduced overall energy consumption.



### **Anti mildew running**

After the air conditioner is powered off, the indoor fan continues operating for approximately 30 seconds to dry the evaporator and internal components, helping prevent moisture retention and mildew formation. This function ensures condensate removal prior to shutdown, maintaining the cleanliness and hygiene of the indoor unit.

### **Indoor self-clean**

Through an automated frosting and defrosting cycle, the HHXI indoor unit effectively removes accumulated impurities, helping restore a cleaner and more hygienic air conditioner.

# Personalized comfort

By activating the "I Feel" function, the HHXI indoor unit adjusts airflow and cooling intensity based on the temperature detected by the remote control, ensuring more precise and personalized comfort.



Technical specifications for multisplit systems

# HAVA PAC

HHXI-25MC/35MC/50MC

Model		HHXI-25MC4Y	HHXI-35MC4M	HHXI-50MC4X
Cooling capacity	kW	2,6	3,2	5,0
Heating capacity	kW	2,7	3,4	5,6
Air flow	m <sup>3</sup> /h	550	550	880
Noise Level (Sound Power)	dB(A)	57	57	60
Noise Level (Sound Pressure)	dB(A)	40/28	40/28	46/33
Net Dimension - Indoor Unit (WxHxD)	mm	790×255×200	790×255×200	890×300×220
Net Weight - Indoor Unit	kg	7,1	7,1	10
Diameter(Liquid)	mm	Φ6.35(1/4")	Φ6.35(1/4")	Φ6.35(1/4")
Diameter(Gas)	mm	Φ9.52(3/8")	Φ9.52(3/8")	Φ12.7(1/2")

## + Combination Table for multisplit systems

Model	HHXI		
	2,5 kW	3,5 kW	5,0 kW
HHXE-2MC52U4X	✓	✓	
HHXE-3MC72U4J	✓	✓	✓
HHXE-4MC81U4J	✓	✓	✓
HHXE-5MC105U4Q	✓	✓	✓